## **SKID LOADERS**



**GEHL**®

Capacities		Metric
Operating Capacity At 50% Tipping Load		612.34 kg
Rated Operating Capacity with Optional Counterweight		680 kg
Operating Weight		2383.62 kg
Fipping capacity		1224.69 kg
Neight and dimensions		
Overall Operating Height - Fully Raised	h27	3670.30 mm
leight to Hinge Pin – Fully Raised	h28	2790 mm
Overall Height to top of ROPS	h17	1930 mm
Dump angle at full height	a5	40 °
Dump height	h29	2120 mm
Overall length with bucket	l16	3073.40 mm
ump reach - Full height	r6	591 mm
eat to ground height	h30	871.22 mm
Vheelbase	у	950 mm
Overall width less bucket	b1	1364 mm
Bucket Width	e1	1372 mm
Ground clearance	m4	201 mm
Overall length - Less Bucket	12	2359.66 mm
Clearance Radius - Front with Bucket	b18	1842 mm
Clearance Circle - Front without Bucket	b19	1120 mm
Clearance Circle - Rear	wa1	1372 mm
Performances		
ravel speed (unladen)		12.90 km/h
Vheels		
tandard tires		10.00 x 16.5 HD
ingine		
ngine brand		Yanmar
ngine model		4TNV88
ngine norm		Stage IIIA / Interim Tier 4
iross Power		34.30 kW
let Power		33.20 kW
Max. torque / Engine rotation		146.20 Nm / 1820 rpm
Power source		Diesel
Battery voltage		12 V
itarter		2.30 kW
lydraulics		
standard flow - Auxiliary hydraulics		63.60 l/min
ank capacities		
ueltank		59.40 l
Displacement		2.19 l
loise and vibration		
Noise to environment (LwA)		101 dB
Nhole-Body Vibration (ISO 2631-1)		0.81 m/s <sup>2</sup>
fibration on hands/arms		< 1.77 m/s²





Siège Social P.O. Box 179 - One Gehl Way - West Bend, WI, USA 53095 Tel: (262) 334-9461 - Fax: (262) 338-7517 www.gehl.com



This brochure describes versions and configuration options for Gehl products which may be fitted with different equipment. The equipment described in this brochure may be standard, optional or not available depending on version. Gehl reserves the right to change the specifications shown and described at any time and without prior warning. The manufacturer is not liable for the specifications given. For more information, contact your Gehl dealer. Non-contractual document. Product descriptions may differ from actual products. List of specifications is not comprehensive. The logos and visual identity of the company are the property of Gehl and may not be used without authorization. All rights reserved. The photos and diagrams contained in this brochure are provided for information only.

MANITOU EQUIPMENT AMERICAS, LLC - Limited company with board of directors - Share capital: 39,668,399 euros - 857 802 508 RCS West Bend