RT165


TRACK LOADERS



GEHL.

RT165 Created on 10 Ju	ly 2024 at 10:16:05	AM UTC
------------------------	---------------------	--------

	killes ciculo	d on 10 July 2024 at 10:16:05 AM UTC
Capacities		Metric
Operating Weight		3638 kg
Operating Capacity at 35% Tipping Load		748.42 kg
Operating Capacity At 50% Tipping Load		1069 kg
Tipping capacity		2139 kg
Weight and dimensions		, and the second s
Overall Operating Height - Fully Raised	h27	4008 mm
Height to Hinge Pin – Fully Raised	h28	3038 mm
Reach - Fully Raised	dp1	641 mm
Dump angle at full height	a5	39 °
Dump Height - Fully Raised	h29	2329 mm
Maximum Rollback Angle - Fully Raised	a4	98 °
Overall Height to top of ROPS	h17	1969 mm
Overall length with bucket	l16	3205 mm
Overall Length without Bucket	l1	2393 mm
Specified Height	h31	1638 mm
Reach at Specified Height	r4	559 mm
Dump angle at specified height	a17	70 °
Maximum Rollback Angle at Ground	a17	28 °
Carry Position	d5	198 mm
-	a14	28 °
Maximum Rollback Angle at Carry Position		
Digging Position	h32	53 mm 185 mm
Ground clearance	m4	1407 mm
Track gauge	b10	
Track Shoe Width	b20	400 mm
Crawler base	y2	1265 mm
Overall width less bucket	b1	1727 mm
Bucket Width	e1	1676 mm
Clearance Radius - Front with Bucket	b18	1979 mm
Clearance Circle - Rear	wa1	1440 mm
Track Type / Track Rollers / Roller Type		Rubber / 4 / Steel
Performances		
Ground Speed - Single Speed		10.50 km/h
Drawbar Pull/Tractive Effort		4345 kg
Bucket Breakout - Tilt Cylinder		1919 kg
Bucket Breakout - Lift Cylinder		2295 kg
Engine		
Engine brand		Yanmar
Engine model		4TNV98C-NMS2
Motor Type		Radial Piston
Gross Power / Power		51.70 kW @ 2500 rpm
I.C. Engine power rating		69.30 Hp
Battery voltage		12 V
Cold Cranking Amps at Temperature (CCA)		950 A
Alternator - Voltage / Ampere		112 V / 100 A
Hydraulics		
Standard flow - Auxiliary hydraulics		71 l/min
High-Flow Auxiliary Hydraulics – Option		113 l/min
Tank capacities		
Oil Pan Capacity		91
Hydraulic oil tank capacity		39 l
Fuel tank		62.50 l
Displacement / Number of cylinders		3.30 l / 4



This brochure describes versions and configuration options for Gehl products which may be fitted with different equipment. The equipment described in this brochure may be standard, optional or not available depending on version. Gehl reserves the right to change the specifications shown and described at any time and without prior warning. The manufacturer is not liable for the specifications given. For more information, contact your Gehl dealer. Non-contractual document. Product descriptions may differ from actual products. List of specifications is not comprehensive. The logos and visual identity of the company are the property of Gehl and may not be used without authorization. All rights reserved. The photos and diagrams contained in this brochure are provided for information only.

MANITOU EQUIPMENT AMERICAS, LLC - Limited company with board of directors - Share capital: 39,668,399 euros - 857 802 508 RCS West Bend