TRACK LOADERS



GEHL®

	RITYS Created Off	RT195 Created on 10 July 2024 at 10:16:18 AM UTO	
Capacities		Metric	
Rated Operating Capacity		885 kg	
Rated Operating Capacity with Optional Counterweight		2657 kg	
Operating Weight		3697 kg	
Unladen weight		3422 kg	
Operating Capacity At 50% Tipping Load		1264 kg	
Tipping capacity		2527 kg	
Weight and dimensions			
Overall Operating Height - Fully Raised	h27	4018 mm	
Height to Hinge Pin – Fully Raised	h28	3048 mm	
Dump reach - Full height	r6	648 mm	
Dump angle at full height	a5	39 °	
Overall Height to top of ROPS	h17	1979 mm	
Overall length with bucket	l16	3279 mm	
Departure angle	a2	27 °	
Ground clearance	m4	188 mm	
Overall width less bucket	b1	1746 mm	
Bucket Width	e1	1778 mm	
Clearance Radius - Front with Bucket	b18	2063 mm	
Clearance Circle - Rear	wa1	1509 mm	
Engine		1307 11111	
Engine brand		Yanmar	
Engine model		4TNV98C-NMS2V	
Gross Power		51.70 kW	
Net Power		51 kW	
Max. torque / Engine rotation		241 Nm @ 2500 rpm	
I.C. Engine power rating - Power		68.40 Hp / 51 kW	
Battery voltage		12 V	
Accessory plug		12 V	
Alternator - Ampere		100 A	
Transmission		100 A	
Transmission type		Hydrostatic	
Hydraulics		nyurostatic	
		71 l/min	
Standard flow - Auxiliary hydraulics		380 bar	
Auxiliary Hydraulic Pressure			
High-Flow Auxiliary Hydraulics – Option		113 l/min	
High-Flow Auxiliary Hydraulics Pressure – Option		420 bar	
Tank capacities		0.51	
Hydraulic oil tank capacity		36 l	
Fuel tank		58.70 l	
Coolant system capacity		12.90 l	
Displacement / Number of cylinders		3.30 l / 4	
Noise and vibration			
Noise to environment (LwA)		101.40 dB	
Noise at driving position (LpA)		82 dB	
Whole-Body Vibration (ISO 2631-1)		1.10 m/s ²	





Siège Social P.O. Box 179 - One Gehl Way - West Bend, WI, USA 53095 Tel: (262) 334-9461 - Fax: (262) 338-7517 www.gehl.com



This brochure describes versions and configuration options for Gehl products which may be fitted with different equipment. The equipment described in this brochure may be standard, optional or not available depending on version. Gehl reserves the right to change the specifications shown and described at any time and without prior warning. The manufacturer is not liable for the specifications given. For more information, contact your Gehl dealer. Non-contractual document. Product descriptions may differ from actual products. List of specifications is not comprehensive. The logos and visual identity of the company are the property of Gehl and may not be used without authorization. All rights reserved. The photos and diagrams contained in this brochure are provided for information only.

MANITOU EQUIPMENT AMERICAS, LLC - Limited company with board of directors - Share capital: 39,668,399 euros - 857 802 508 RCS West Bend